

# **ACCESSORIES**

# INTEGRATED EXHAUSTS

LE120 & LE140+

Designed especially for Gravograph applications, the integrated exhausts LE120 & LE140 + are essential accessories for the use of **LS100 Laser**. They are compatible with marking, engraving and cutting noxious material such as rubber and acrylic, **without any repulsive odour**.



# Benefits of integrated exhausts:

# ■ Compact & Integrated

As all our Integrated Exhausts, the concept is **self containment** and minimized floor space requirement. The exhaust becomes the base of the laser, making the sytem compact and aesthetic in the workshop.

#### Safe

Laser systems are used to a wide variety of materials. During these processes, gases, vapours and dusts are and can be in most cases classified as harmful if inhaled. LE 120 and LE 140+ are The solution to remove these airborne contaminants by provision of a fume extraction and filtration system.

#### Productive & Cost effective

Due to their cleanable pre-filters and effective HEPA filter, Gravograph exhausts offer an extremely efficient filtration therefore increasing the life span of the important parts of the machine (metallic parts and lenses).

## Quality

With the LE140+ and LE120 extractors, and the vacuum flow rates ranging from 200 to 400m3/h, the system enables to reach the best engraving quality.

# **Applications:**

$\mathscr{S}$ = marking, engraving $\mathscr{K}$ :	= cutting $\varnothing$ = not advised	🏿 = forbidden	
	LS100 30W & LE 120	LS100 30 W & LE 140 +	
PVC	<b>®</b> ×	<b>®</b> *	
Mirror, Marble, Stone, Glass	P		
Porcelain, Ceramics, Enamel			
Metals (brass, alu)		ø	
Plastic, Acrylics, Wood		<b>№</b> + <b>※</b>	
Foil, Paper, Leather	<b>№</b> + <b>※</b>	<b>№</b> + <b>※</b>	
Rubber stamp sheets	⊗	<b>№</b> + <b>※</b>	
Caoutchouc, Foam, Textiles	⊗	<b>№</b> + <b>×</b>	
Anodised metal, Cardboard	⊗	P	

# **Technical Features:**

	LE	LE 120		LE 140 +	
	20L - 230V	20L - 115V	40L - 230V	40L - 115V	
Dimensions	700 x 644	700 x 644 x 730 mm		700 x 644 x 730 mm	
Weight	7:	71 kg		83 kg	
Max. air flow	400	400m3/h		400m3/h	
Flow control	١	Yes		Yes	
Max. static pressure	4	4kPa		4kPa	
Noise level	58	58 dB		58 dB	
Switch (On/Off)	١	Yes		Yes	
VariColour warning system	١	Yes		Yes	
Nomber of pre-filter pleats		3		6	
Combined Filter	20	20 liters 40 liters		ers	
Frequency	50 /	50 / 60 Hz 50 /		0 Hz	

# **GRAVOGRAPH**

B.P. 36 56 Avenue Jean Jaurès F-10601 La Chapelle St Luc Cedex

Tel: 03 25 41 65 65 Fax: 03 25 79 04 25

www.gravograph.com